UNIFORM LIGHTING FRAMES



SACKLIGHT
Designed and Made in Italy



Index

04 | What is HALO

05 |Size

06 |Technical specs

07 |Sections

08-09 |Ceiling & Wall recessed by magnets and iron plate

10-11 |Installation manual Ceiling & Wall recessed

12-13 |Ceiling & Wall examples by magnets and iron plate

HALO

The architecture of light.

The Backlight HALO line is a versatile and elegant lighting solution designed to create a perimeter lighting effect. Its main uses include lighting around mirrors, elevator lighting, and more generally, can be installed on both walls and ceilings, as well as used as suspensions.


These lamps are produced in a single, custom-made piece, with the possibility of being made in irregular shapes.

The lamps in the HALO line stand out from other similar products for their construction that avoids the visibility of common joints normally present at the corners.


Thanks to this, HALO guarantees perfect light uniformity and an impeccable result.

It is possible to choose the color temperature of the light among various available options, customizing the light according to design needs and creating a perfect atmosphere for every occasion.

Sizes




Available in custom width under request




Technical Specs

COLOR TEMPERATURE	2000 K 2700 K 3000 K 3500 K 4100 K 5000k
	Tun. White Tun. White Custom range 1800-3200K 2400-4100K Tun. White* RGB RGBW* RGBWW* DIM to WARM*
	*Under request for a minimum order quantity to be define.
CRI	> 95
INPUT VOLTAGE	24VDC
DRIVER	AC DC 24V DC OUTPUT (class 2 Power Unit)
DIMMABILITY	by all existing systems (ELV/MLV, 0-10V, DALI, LUTRON, DMX)
POWER	STANDARD BRIGHT 14 W per linear mt of perimeter (4,5 W per linear FT of perimeter)
CONSUMPTION	HIGH BRIGHT 28 W per linear mt of perimeter (9.0 W per linear FT of perimeter)
LUMEN	STANDARD BRIGHT 980lm per linear mt (315 lm per linear FT of perimeter)
DELIVERED	HIGH BRIGHT 1960lm per linear mt of perimeter (630 lm per linear FT of perimeter)
IP GRADE	IP40 for Dry Location (IP54 for Damp Location under request)
DIMENSIONS	Short sideMM 203.2 to 2006.6 mm INCHES 8.0 to 79.0 in
	Long sideMM to 3048.0 mm INCHES 4.0 to 120.0 in
	Width of light 15.24 mm (0.6") 30.48 mm (1.2") 40.64 mm (1.6") 76.2 mm (3") 152.4 mm (6") CUSTOM ON 203.2 mm (8") So.8 mm (1.4") 50.8 mm (2") 101.6 mm (4") 203.2 mm (8") REQUEST
LIFE TIME	70.000 hrs
WARRANCY	3 Years (36 month)
CERTIFICATIONS	CE ERI o Un us

SECTIONS








CEILING RECESSED MOUNTINGBy magnets and iron plate


WALL RECESSED MOUNTING
By magnets and iron plate


INSTALLATION MANUAL | HALO WALL & CEILING RECESSED MOUNTING by magnets and iron plate



Note: The cup of screws must be less deep then 3mm.

INSTALLATION MANUAL | HALO WALL & CEILING RECESSED MOUNTING by magnets and iron plate





CEILING MOUNTINGBy magnets and iron plate

WALL MOUNTINGBy magnets and iron plate



















Discover all our most famous products that have made and still make lighting history.

MAGIC CLOUD Custom Uniform Lighting Panels

FLUSH Custom Uniform Lighting Bars

HALO Custom uniform Lighting Frames in a single piece

HIDE Line of Uniform Lighting Circles

PILL Plasterboard built-in Square and Round Lights

WETTY WET / IP67 Line

CHIARO Lighting Integration for ARMSTRONG CEILINGS

STAMP Creative light on plasterboard



www.backlightsrl.com

⇒ACKLIGHT

Via Alessandro Volta, 5 20876 Ornago (MB) Italy

+39 039 6010396 www.backlightsrl.com info@backlightsrl.com

